



# CARPET CUSHION

- PROLONGS CARPET LIFE
- VERY HEAVY WEIGHT QUALITY RUBBER UNDERLAY
- SUITABLE FOR PRESTIGIOUS LUXURY AREAS
- EXCELLENT FOR IMPACT SOUND REDUCTION
- EASY LIFT HALF SIZE ROLLS

## RECOMMENDED AREAS OF USE

DOMESTIC - SUITABLE FOR LUXURY USE AREAS SUCH AS LIVING ROOMS, AND BEDROOMS - AREAS OF MODERATE WEAR

Manufactured in the UK to BS 5808:1991 & BS EN 14499:2015

## STANDARD SPECIFICATIONS

TOP SURFACE	Printed stitch bonded white crepe paper	
BOTTOM SURFACE	Sponge Rubber	
NOMINAL THICKNESS	11.00 mm	
NOMINAL ROLL WEIGHT	31.0 kg	68.3 lb
WEIGHT PER UNIT AREA	4114 g/m <sup>2</sup>	121 oz/yd <sup>2</sup>
ROLL LENGTH	5.50 m = 7.5sq.m	18.0 ft
ROLL WIDTH	1.37 m	54 in
GUARANTEE	Lifetime of the initial carpet installation (when used in recommended areas)	

## BS. 5808 : 1991 TEST RESULTS - BRITISH STANDARD FOR CARPET UNDERLAYS

END USE CLASSIFICATION	BS.5808	L/U
WORK OF COMPRESSION AFTER 1000 IMPACTS	BS.4098	>170 J/m <sup>2</sup>
RETENTION OF WORK OF COMPRESSION	BS.4098	>80 %
LOSS IN THICKNESS AFTER STATIC LOADING	BS.4939	<10.00 %
LOSS IN THICKNESS AFTER DYNAMIC LOADING	BS.4052	<10.00 %
RESISTANCE TO CRACKING	BS.5808 (A)	Pass

## OTHER RELEVANT TESTS

THERMAL RESISTANCE (TOG RATING)	BS.4745	1.2 tog
IMPACT SOUND IMPROVEMENT INDEX (Test/Rated to BS EN ISO 140-8 / BS EN ISO 717-2)		42 dB

ISSUE 1 01-JANUARY-17

## DISCLAIMER

Whilst every effort is made to ensure its accuracy, the data on this sheet is meant for information purposes only. The typical properties listed are the result of extensive laboratory tests, but since Ball & Young has no control over the end use of each material, we cannot guarantee these results are obtained in practice. Users should conduct their own tests to determine the suitability of each material to its intended application.

  
**Ball & Young Ltd**  
 A Vita Group Company