

CLOUD



CLOUD 9 CIRRUS

- CLOUD 9 APT
- EXCELLENT THERMAL AND SOUND REDUCTION PROPERTIES
- EXCELLENT RECOVERY CHARACTERISTICS
- SUITABLE FOR WOOD BLOCK FLOORS

RECOMMENDED AREAS OF USE

SUITABLE FOR LUXURY DOMESTIC AREAS SUCH AS LIVING ROOMS AND BEDROOMS.

Manufactured in the UK to BS 5808:1991 & BS EN 14499:2015

STANDARD SPECIFICATIONS

TOP SURFACE	Printed stitch bonded crepe paper	
BOTTOM SURFACE	White non-woven fabric	
NOMINAL THICKNESS	9.00 mm	
NOMINAL ROLL WEIGHT	15.7 Kg	34.6 lb
WEIGHT PER UNIT AREA	1042 g/M ²	31 oz/yd ²
ROLL LENGTH	11.0 m	36.0 ft
ROLL WIDTH	1.37 m	54 in
GUARANTEE	Lifetime of the initial carpet installation (when used in recommended areas)	
CORE DENSITY	100 Kg/M ³	
PRODUCT DENSITY	116 Kg/M ³	

BS. 5808 : 1991 TEST RESULTS - BRITISH STANDARD FOR CARPET UNDERLAYS

END USE CLASSIFICATION	BS.5808	L/U
WORK OF COMPRESSION AFTER 1000 IMPACTS	BS.4098	>150 J/m ²
RETENTION OF WORK OF COMPRESSION	BS.4098	>80 %
LOSS IN THICKNESS AFTER STATIC LOADING	BS.4939	<5.00 %
LOSS IN THICKNESS AFTER DYNAMIC LOADING	BS.4052	<5.00 %
RESISTANCE TO CRACKING	BS.5808 (A)	Pass

FIRE RESISTANCE TESTS

HOT METAL NUT TEST	BS.4790	Pass - Medium radius of effect
--------------------	---------	--------------------------------

INDOOR AIR QUALITY TEST

TESTED TO ISO16000		
FRENCH VOC EMISSION CLASS LABEL	A+	
CONFORMS TO REQUIREMENTS DIBT (OCTOBER 2010) AND AGBB (JUNE 2012)		

OTHER RELEVANT TESTS

THERMAL RESISTANCE (TOG RATING)	BS 4745	2.5 TOG
IMPACT SOUND IMPROVEMENT INDEX (Test/Rated to BS EN ISO 140-8 / BS EN ISO 717-2)		39 -41dB



ISSUE 6 02 -JUNE -14

DISCLAIMER

Whilst every effort is made to ensure its accuracy, the data on this sheet is meant for information purposes only. The typical properties listed are the result of extensive laboratory tests, but since Ball & Young has no control over the end use of each material, we cannot guarantee these results are obtained in practice. Users should conduct their own tests to determine the suitability of each material to its intended application.



CLOUD 9 CIRRUS